

ASSEMBLY: BOOSTER & RISER 150mm QUAD

**Booster: 2 x Dual c/w 150mm
Riser & 150mm Gear Operated
Butterfly Valve**

PRODUCT CODE

QB150/RBV

BRIGADE CONNECTIONS

Storz
5v thread
CFA thread

DIMENSIONS

WIDTH - 420mm overall
DEPTH - 520mm
HEIGHT - 1120mm overall

APPROVALS

PIPE: AS 1074 Hot Dipped Gal.
BOOSTER: AS 2419.3
BUTTERFLY VALVE: FM/UL Listed
COUPLINGS: FM/UL Listed

WORKING PRESSURE

COUPLINGS: 5175kpa
BOOSTER: 1400kpa
BUTTERFLY VALVE: 1207kpa

WORKING PRESSURE

COUPLINGS: 5175kpa
BOOSTER: 1400kpa
BUTTERFLY VALVE: 1207kpa

INSTALLATION

Connect to service 100mm above finished ground level with copper x roll groove adaptors or flanges (either supplied)

OPTIONS AVAILABLE

Roll groove connection on riser
Flanged (E) connection on riser
varying riser heights fabricated to order

MATERIAL

BOOSTER - Epoxy lined cast iron
BUTTERFLY VALVE: Body - Ductile iron
nylon coated
STEM - Stainless steel
DISC - Bronze
COUPLINGS - Galvanised
RISER - Hot dipped gal.

