

ASSEMBLY: BOOSTER & RISER 100mm DUAL

**Booster: Bottom Entry c/w 100mm
Riser & 100mm Gear Operated
Butterfly Valve**

PRODUCT CODE

DB100/RBV

BRIGADE CONNECTIONS

All Australian Fire
Authorities Available

DIMENSIONS

WIDTH - 448mm overall
DEPTH - 355mm
HEIGHT - 1000mm overall

APPROVALS

PIPE: AS 1074 Hot Dipped Gal.
BOOSTER: AS 2419.3 (Approved)
BUTTERFLY VALVE: UL/FM Listed
COUPLINGS: UL/FM Listed

WORKING PRESSURE

COUPLINGS: 2068 kPa
BOOSTER: 1400 kPa
BUTTERFLY VALVE: 2068 kPa

INSTALLATION

Connect to service 100mm above finished
ground level with copper x roll groove
adaptors or flanges (either supplied)

OPTIONS AVAILABLE

Roll groove connection on riser
Flanged (E) connection on riser
Varying riser heights fabricated
to order

MATERIAL

BOOSTER - Epoxy lined cast iron
BUTTERFLY VALVE: Body - Ductile iron
nylon coated
STEM - Stainless steel
DISC - EPDM coated

COUPLINGS - Galvanised
RISER - Hot dipped gal.

