

# ASSEMBLY: BOOSTER & RISER 150mm QUAD

**Booster: 2 x Dual c/w 150mm  
Riser & 150mm Gear Operated  
Butterfly Valve**

## PRODUCT CODE

DDQB150/RBV

## APPROVALS

PIPE: AS 1074 Hot Dipped Gal.  
BOOSTER: AS 2419.3 (Approved)  
BUTTERFLY VALVE: UL/FM Listed  
COUPLINGS: UL/FM Listed

## INSTALLATION

Connect to service 100mm above finished ground level with copper x roll groove adaptors or flanges (either supplied)

## BRIGADE CONNECTIONS

All Australian Fire  
Authorities Available

## WORKING PRESSURE

COUPLINGS: 2068 kPa  
BOOSTER: 1400 kPa  
BUTTERFLY VALVE: 2068 kPa

## OPTIONS AVAILABLE

Roll groove connection on riser  
Flanged (E) connection on riser  
Varying riser heights fabricated to order

## DIMENSIONS

WIDTH - 473mm overall  
DEPTH - 520mm  
HEIGHT - 1120mm overall

## MATERIAL

BOOSTER - Epoxy lined cast iron  
BUTTERFLY VALVE: Body - Ductile iron  
nylon coated  
STEM - Stainless steel  
DISC - EPDM coated  
COUPLINGS - Galvanised  
RISER - Hot dipped gal.

