

# FIRE EXTINGUISHERS

CARBON DIOXIDE: BE  
 PRODUCT CODE: VARIOUS

PRODUCT CODE  
 FXC

## CARBON DIOXIDE



**B: FLAMMABLE LIQUIDS**



**E: ELECTRICAL EQUIPMENT**



**2.0 kg**

**3.5 kg**

**5.0 kg**

**APPLICATIONS:** CO<sub>2</sub> Extinguishers are designed for use on E Class fires, involving energised electrical equipment such as switchboards, electrical motors and electronic equipment. They are also suitable for use on B Class Flammable Liquid fires. CO<sub>2</sub> is a gas that penetrates and spreads to all parts of the fire area. These extinguishers are more effective when used indoors or where wind is not a factor, however they are NOT recommended for use within confined spaces.

**CONSTRUCTION:** Our CO<sub>2</sub> fire extinguishers feature a lightweight aluminium seamless cylinder which is manufactured to Australian Standards. The robust forged brass chrome plated valves incorporate a pressure relief valve, with a stainless steel handle and lever fitted.

Australian Standards Approval AS1841.6

| CAPACITY<br>kg   | CYLINDER<br>DIAMETER<br>mm | HEIGHT<br>mm | OVERALL<br>MASS<br>(Approx) | DISCHARGE<br>TIME (Sec) | RATING | MODEL |
|------------------|----------------------------|--------------|-----------------------------|-------------------------|--------|-------|
| 2.0              | 110                        | 520          | 5.1                         | 8 - 9.5                 | 5B:E   | FXC20 |
| 3.5<br>with hose | 140                        | 570          | 8.8                         | 10.5 - 14               | 10B:E  | FXC35 |
| 5.0<br>with hose | 150                        | 660          | 11.7                        | 13 - 16                 | 10B:E  | FXC50 |

\*All extinguishers and blankets supplied with signage\*