

# FIRE HOSE REEL

LKS MARK 111 ALL STAINLESS STEEL  
 PRODUCT CODE: #FHRASS3619



Australian Standard



Quality ISO 9001

### DIMENSIONS

Diameter: 555mm  
 Depth: 239mm

### MANUFACTURING

Made to AS/NZS 1221

### RECOMMENDATION

Mounting the Isolation Valve at a height of 1060mm will achieve the Hose Reel centre height of 1500mm

If the minimum Isolation Valve height of 900mm is required, the length of the back pipe will need to be extended on site

Radial Clearance of not less than 100mm must be maintained around the Hose Reel Plates and Isolating Valve

### INSTALLATION

Drum Centre: 1400 - 2400mm

Isolation Valve Centre: 900 - 1100mm

### OPTIONS

Various Side Plate Colours

### MATERIAL

Side Plates: Powder Coated Signal Red

Side Plates: Stainless Steel #316

Spacer Pins: Stainless Steel #316

Fire Reel Hose: P.V.C 19mm Internal Diameter

Hose Length: 36 metres

Nozzle: Jet/Lever Action Stainless Steel #316

Guide Arm: Swivel. Stainless Steel #316

Bracket: Easi-Fit. Stainless Steel #316

Inlet Pipe: Stainless Steel #316

Barrell Union: F&F. Stainless Steel #316

Spindle: Stainless Steel #316

Waterway & Support Plate: Stainless Steel #316

Isolation Valve: Stainless Steel #316 25mm

(M&F) Nozzle Interlock & Handle

\*All measurements are a guide only - for accurate measurements please contact KlineFire\*

