

FIRE HOSE REEL

LKS MARK 111 STAINLESS STEEL: HEAVY DUTY BEARING

PRODUCT CODE: #FHRSS3619HD



Australian Standard

Quality ISO 9001

DIMENSIONS

Diameter: 555mm

Depth: 239mm

MANUFACTURING

Made to AS/NZS 1221

RECOMMENDATION

Mounting the Isolation Valve at a height of 1060mm will achieve the Hose Reel centre height of 1500mm

If the minimum Isolation Valve height of 900mm is required, the length of the back pipe will need to be extended on site

Radial Clearance of not less than 100mm must be maintained around the Hose Reel Plates and Isolating Valve

INSTALLATION

Drum Centre: 1400 - 2400mm

Isolation Valve Centre: 900 - 1100mm

OPTIONS

Various Side Plate Colours

MATERIAL

Side Plates: Powder Coated Signal Red

Side Plates: Stainless Steel #316

Spacer Pins: Stainless Steel #316

Fire Reel Hose: P.V.C 19mm ID - 36m Length

Nozzle: Jet/Spray Plastic

Guide Arm: Swivel. Stainless Steel #316

Bracket: Easi-Fit. Galvanized

Inlet Pipe: Galvanized

Barrell Union: F&F. Stainless Steel #316

Spindle: DR Brass

Waterway: DR Brass - Support Disc S/S.

Isolation Valve: DR Brass. 25mm (M&F) #304

Stainless Steel Interlock & Handle

Bearing: VB205-16 Stainless Steel and Housing

All measurements are a guide only - for accurate measurements please contact KlineFire

