# FIRE EXTINGUISHERS

**CARBON DIOXIDE: BE PRODUCT CODE: VARIOUS** 



### PRODUCT CODE **FXC**

## **CARBON DIOXIDE**



**B: FLAMMABLE** LIQUIDS



E: ELECTRICAL **EQUIPMENT** 



2.0 kg

3.5 kg

5.0 kg

#### **APPLICATIONS:**

CO<sub>2</sub> Extinguishers are designed for use on E Class fires, involving energised electrical equipment such as switchboards, electrical motors and electronic equipment. They are also suitable for use on B Class Flammable Liquid fires. CO<sub>2</sub> is a gas that penetrates and spreads to all parts of the fire area. These extinguishers are more effective when used indoors or where wind is not a factor, however they are NOT recommended for use within confined spaces.

Our CO<sub>2</sub> fire extinguishers feature a lightweight aluminium seamless cylinder **CONSTRUCTION:** which is manufactured to Australian Standards. The robust forged brass chrome plated valves incorporate a pressure relief valve, with a stainless steel handle and lever fitted.

## Australian Standards Approval AS1841.6

CAPACITY kg	CYLINDER DIAMETER mm	HEIGHT mm	OVERALL MASS (Approx)	DISCHARGE TIME (Sec)	RATING	MODEL
2.0	110	520	5.1	8 - 9.5	5B:E	FXC20
3.5 with hose	140	570	8.8	10.5 - 14	10B:E	FXC35
5.0 with hose	150	660	11.7	13 - 16	10B:E	FXC50

<sup>\*</sup>All extinguishers and blankets supplied with signage\*

