

# FIRE HOSE REEL

## LKS MARK 111 HEAVY DUTY BEARING

PRODUCT CODE: HRP3619/HD



### DIMENSIONS

Diameter: 555mm  
Depth: 239mm

### TESTING

As per AS/NZS 1221

### RECOMMENDATION

Mounting the Isolation Valve at a height of 1060mm will achieve the Hose Reel centre height of 1500mm

If the minimum Isolation Valve height of 900mm is required, the length of the back pipe will need to be extended on site

Radial Clearance of not less than 100mm must be maintained around the Hose Reel Plates and Isolating Valve

### INSTALLATION

Drum Centre: 1400 - 2400mm  
Isolation Valve Centre: 900 - 1100mm

### OPTIONS

Various Side Plate Colours

### MATERIAL

Side Plates: CR-F Steel. Signal Red  
Spacer Pins: Mild Steel. Zinc Plated  
Fire Reel Hose: P.V.C 19mm Internal Diameter  
Hose Length: 36 Meters  
Nozzle: Jet Lever Action. DR Brass  
Guide Arm: Swivel. Zinc Plated  
Bracket: Easi-Fit. Galvanized  
Inlet Pipe: Galvanized  
Barrell Union: F&F. Galvanized  
Spindle: DR Brass  
Waterway: DR Brass  
Support Disc: #316 Stainless Steel  
Isolation Valve: DR Brass. 25mm (M&F) #304  
Stainless Steel Interlock & Handle  
Bearing: UB205-16 Mild Steel and Housing

\*Sizes may vary due to supply of product, contact office to confirm\*

